MULTI COVER AIR PLUS

DESCRIPTION

MULTI COVER AIR PLUS is a self-adhering fleece used to temporarily protect floors and stairs. The fleece consists of two layers. The anti-slip bottom layer is non-woven and has a special water-resistant adhesive layer. This ensures it always remains fixed in place on the floor. The top layer allows any residuale moisture to evaporate from the underlying floor. The top of this membrane is waterproof. MULTI COVER AIR PLUS can be placed quickly and easily to protect floors and stairs.

APPLICATIONS

- Covering for hard floors
- Covering for lacquered stairs
- Covering for prefabricated concrete
- Covering for prefabricated stairs and balconies
- Covering for parquet floors and lacquered stairs

CHARACTERISTICS

- Quick and easy to use
- Safe to walk on thanks to the anti-slip layer
- Shock-absorbing and waterproof top layer
- Permeable bottom layer
- Reusable
- Suitable for covering starrs thanks to the convenient format
 -

TECHNICAL DATA

Application duration	3 months (max 40°C)
Storage	12 months (5° - 30°C) (dry, no direct sunlight)
Thickness	2,5mm +/- 10%
Weight	160 gr/m2
Tensile Strengt (MD)	Min. 100N/5cm
Tensile Strengt (CD)	Min. 100N/5cm
Elongation @ Fmax (MD)	Max. 125%
Elongation @ Fmax (CD)	Max. 150%
Skid ability	150 N / A4 Sample
Water vapour permeability	70 gr/m2/24hr
Winding	Reversed sound (Glue on the outside)
Core	Carboard Tube

COMPOSITION

Material	Non-woven produced with 100% PES fiber
Adhesive	Acrylic waterbased
Colour	White
Laminated	Breathable PE-film

Easydek® products are tested on a regular basis. The technical information mentioned is offered on the basis of knowledge, insight, and experiences from practice. The stated data is not binding as aspecification and should be considered as a guideline. Easydek B.V. cannot provide any guarantee or warranty about the suitability for a particular application or the use of this product. When using this product the user is always responsible. Before use, the product must always be tested. Deviations in the information can be caused by various environmental factors and deviations in



the measuring equipment and methods used. Easydek B.V. is not liable for damage and consequential damage as a result of the use of this product.